

## Declaration of Performance

1. Identification code of the product-type: **VARA PLUS**
2. Type number as required pursuant to Article 11(4) of the Regulation (EU) No 305/2011: **VARA PLUS**
3. Intended use of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:  
**Plastic and rubber vapour control layers - EN 13984**
4. Registered trade name and contact address of the manufacturer as required pursuant to Article 11(5): **Partel**  
|17 Claregalway Corporate Park | Claregalway| Co. Galway | Ireland | H91 X510
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2): **Not applicable.**
6. System of assessment and verification of constancy of performance of the construction product as set out in Annex V: **System 3.**
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard: **SGS INTRON BV (NB 1939) and BTG (NB 0339) performed an initial type test under system 3 and issued test reports.**
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued: **Not applicable.**
9. Declared performance:

Essential Performances	Method	Performances	Min tolerance	Max tolerance	Harmonised technical specification
Resistance to fire (euroclass)	EN 13501-1	E	-	-	EN 13984
Water tightness at 2kPa	EN 1928	Pass	-	-	
Water vapour transmission Sd (m)	EN 1931	8	7	15	
Sd (m) min/max		0,4 - 30			
Tensile force, longitudinal (N/50mm)	EN 12311-1	350	330	370	
Tensile force, transverse (N/50mm)	EN 12311-1	315	295	335	
Elongation, longitudinal (%)	EN 12311-1	20	15	25	
Elongation, transverse (%)	EN 12311-1	20	15	25	
Tear resistance, longitudinal (N)	EN 12310-1	350	325	385	
Tear resistance, transverse (N)	EN 12310-1	375	350	420	
Durability against aging: Water vapour resistance	EN 1296/ EN 1931	Pass	-	-	
Resistance to penetration of air m3/(m2 h 50Pa)	EN12114	0.0	-	-	
Durability against alkali: Tensile force	EN 12311-2	Pass			



10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of Partel

Hugh Whiskey  
Technical and Development