

IZOPERM

PLUS™

Designed to be compatible with all conventional building systems and all insulations.

Extremely strong and functional performance vapour control layer.

- Elastic and Durable
- Reinforced for optimum strength
- High performance airtightness
- Optimum Sd value for most constructions
- Durable towards UV and humidity ageing.

COLOUR	WHITE
WEIGHT	100
SD- VALUE	5
VAPOUR PERMEANCE	0.69
SURFACE BURNING CHARACTERISTICS	CLASS A
REACTION TO FIRE	E
WATER RESISTANCE	W1
TENSILE STRENGTH MD	285
TENSILE STRENGTH CD	385
ELONGATION MD	15
ELONGATION CD	15
NAIL TEAR RESISTANCE MD	260
NAIL TEAR RESISTANCE CD	246
TEMP RESISTANCE	-40 °F TO 80 °C -40 °F TO 212 °F
CE LABELLING	AVAILABLE

HIGH
PERFORMANCE
BUILDING
PROTECTION
SYSTEMS

1.5m X
50m
= 75m²

59'-1/16" X 164'-1/2" = 807 SF



WWW.PARTEL.COM
SALES@PARTEL.COM
TEL: 0818 33 33 55



WWW.PARTEL.CO.UK
SALES@PARTEL.CO.UK
TEL: 02037 401918



WWW.PARTEL.IE
SALES@PARTEL.IE
TEL: 0818 33 33 55

PRODUCED BY:

PARTEL
CLAREGALWAY CORPORATE PARK,
CLAREGALWAY, CO. GALWAY,
IRELAND. H91 R85P



IZO PERM

PLUS™

Designed to be compatible with all conventional building systems and all insulations.

Extremely strong and functional performance vapour control layer.

- Elastic and Durable
- Reinforced for optimum strength
- High performance airtightness
- Optimum Sd value for most constructions
- Durable towards UV and humidity ageing.

COLOUR	WHITE
WEIGHT	100
SD- VALUE	5
VAPOUR PERMEANCE	0.69
SURFACE BURNING CHARACTERISTICS	CLASS A
REACTION TO FIRE	E
WATER RESISTANCE	W1
TENSILE STRENGTH MD	285
TENSILE STRENGTH CD	385
ELONGATION MD	15
ELONGATION CD	15
NAIL TEAR RESISTANCE MD	260
NAIL TEAR RESISTANCE CD	246
TEMP RESISTANCE	-40 °F TO 80 °C -40 °F TO 212 °F
CE LABELLING	AVAILABLE

HIGH
PERFORMANCE
BUILDING
PROTECTION
SYSTEMS

3.0m X
50m
= 150m²

9' 10-1/3" X 164'-1/2" = 1615 SF



WWW.PARTEL.COM
SALES@PARTEL.COM
TEL: 0818 33 33 55



WWW.PARTEL.CO.UK
SALES@PARTEL.CO.UK
TEL: 02037 401918



WWW.PARTEL.IE
SALES@PARTEL.IE
TEL: 0818 33 33 55

PRODUCED BY:

PARTEL
CLAREGALWAY CORPORATE PARK,
CLAREGALWAY, CO. GALWAY,
IRELAND. H91 R85P



IZOPERM

PLUS™

Designed to be compatible with all conventional building systems and all insulations.

Extremely strong and functional performance vapour control layer.

- Elastic and Durable
- Reinforced for optimum strength
- High performance airtightness
- Optimum Sd value for most constructions
- Durable towards UV and humidity ageing.

COLOUR	WHITE
WEIGHT	100
SD- VALUE	5
VAPOUR PERMEANCE	0.69
SURFACE BURNING CHARACTERISTICS	CLASS A
REACTION TO FIRE	E
WATER RESISTANCE	W1
TENSILE STRENGTH MD	285
TENSILE STRENGTH CD	385
ELONGATION MD	15
ELONGATION CD	15
NAIL TEAR RESISTANCE MD	260
NAIL TEAR RESISTANCE CD	246
TEMP RESISTANCE	-40 °F TO 80 °C -40 °F TO 212 °F
CE LABELLING	AVAILABLE

HIGH
PERFORMANCE
BUILDING
PROTECTION
SYSTEMS

0.75m X
50m
= 37.5m²



WWW.PARTEL.COM
SALES@PARTEL.COM
TEL: 0818 33 33 55



WWW.PARTEL.CO.UK
SALES@PARTEL.CO.UK
TEL: 02037 401918



WWW.PARTEL.IE
SALES@PARTEL.IE
TEL: 0818 33 33 55

PRODUCED BY:

PARTEL
CLAREGALWAY CORPORATE PARK,
CLAREGALWAY, CO. GALWAY,
IRELAND. H91 R85P

