



ACRYLIC PRIMER FOR PRE-TREATMENT OF POROUS-SURFACES

Advantages

Creates an excellent tacky surface to adhere to. ACRAPRIME substrates concrete, plaster, wood, steel, wood base panels OSB, MDF and plywood.

A smoother physical substrate will result in optimum adhesion between tape and surface.

- ✓ Tailored for Partel adhesives and tapes
- ✓ Quick drying = time saving
- ✓ Results in excellent adhesion
- ✓ Can be applied to damp areas
- ✓ Solvent free

Technical Data

Properties	Performance
Contents	1000ml (33.8oz)
Storage stability	2 years
Processing temperature	-10° C to 40° C (-14° F to 104° F)
Material	Dispersion based on polyacrylate
Storage	Cool and dry
Colour	Blue

Fields of Application

ACRAPRIME is used as a primer for porous surfaces like wooden fibreboards, concrete or masonry.

Application Process

Ensure surface is clear from dust, grease, and loose material. The substrate must to be dry and free from frost. Apply ACRAPRIME with a paint brush and allow to dry for 10-30 minutes (depending on temperature). Apply Partel tapes or adhesive products afterwards using some pressure. When applying primer to substrate allow 10% wider primed surface area than the tape. 1 litre can be used to prime 80 m.

"The information provided is based on current knowledge and experience. This data sheet may become invalid and we reserve the right to make changes to designs and processes as we continually improve quality. Processing instructions including full system component details should be adhered to. Visit partel.com for the most up to date information"



www.partel.ie
sales@partel.ie
P: 0818 33 33 55



www.partel.co.uk
sales@partel.co.uk
P: 02037 401918



www.partel.com
sales@partel.com
P: 888 487 1012