



NAIL SEALING TAPE

Hermetically sealing between battens and EXOFORM MONO exterior membranes. Prevents water ingress during construction and afterwards.

Technical Data

Properties	Performance
Carrier	Special PE foam
Adhesive	Acrylic moisture-resistant
Temperature range	-40°C to 80°C -40°F to 176°F
UV tested	6 months
Storage	Cool and dry
Colour	Black
Application temperature	-10° C / 14° F

Advantages

- ✓ High-Performance airtight tape
- ✓ Prevents damage to EXOFORM MONO from screw or nail holes
- ✓ Lifetime design - Optimum level of acrylic adhesive with excellent ageing resistance
- ✓ Solvent-free adhesive
- ✓ Water-repelling carrier— does not absorb water
- ✓ Adheres to timber, masonry, concrete, PVC, metal, Partel membranes
- ✓ Lowest VOC rating in hazardous substance test



General Information

Connections joints should be free from tensile strain. Acrylic based adhesive tapes are pressure activated, sufficient pressure is required to ensure a long lasting bond. A smoother physical substrate will result in optimum adhesion between tape and surface. It is the responsibility of the applicator to check the substrate for suitability, adhesion tests are recommended in non standard situations.

"The information provided is based on current knowledge and experience. This data sheet may become invalid and we reserve the right to make changes to designs and processes as we continually improve quality. Processing instructions including full system component details should be adhered to. Visit partel.com for the most up to date information"



Application Areas

Partel NAILSeal is used to create permanent watertight seal between EXOPERM MONO membranes and battens.

- Recommended for internal and external use

Application Process

Ensure surface is clear from dust, grease, and loose material. The substrate must to be dry and free from frost.

Cut the required length for connection, peel the release liner from tape and with sufficient downward pressure press tape onto substrate to activate acrylic adhesive, use Partel HELPING HAND to apply pressure evenly. Apply the battens afterwards.

"The information provided is based on current knowledge and experience. This data sheet may become invalid and we reserve the right to make changes to designs and processes as we continually improve quality. Processing instructions including full system component details should be adhered to. Visit partel.com for the most up to date information"

"The information provided is based on current knowledge and experience. This data sheet may become invalid and we reserve the right to make changes to designs and processes as we continually improve quality. Processing instructions including full system component details should be adhered to. Visit partel.com for the most up to date information"



www.partel.ie
sales@partel.ie
P: 0818 33 33 55



www.partel.co.uk
sales@partel.co.uk
P: 02037 401918



www.partel.com
sales@partel.com
P: 888 487 1012