

## Outer Hoods

### Beschreibung und Funktionen

The outer hood serves as a solution for increased sound protection requirements and weather conditions. It is used instead of the conventional outer grille on all components of the 160 series, for the exhaust air fans RA 15-60 and AB 30/60, the e<sup>2</sup> series as well as the outer wall air vent ALD and ALD-S.

For the ego and the Nexxt the dual channel outer hood can be used.

The flow through the screen takes place at the bottom; an insect protection is integrated.

Through the use of the outer hood, a significant improvement or increase in the standard sound level difference can be achieved. All things considered, the decisive improvement depends on the entire component (window, wall, ETICS, etc.). The screen is thus also suitable for particularly high noise areas.

Order No.:	1/HWE	040 020
	1/HAZ	040 021
	1/HWE-2	040 107
	1/HAZ-2	040 108

### Installation

The installation is carried out by screwing and doweling the frame onto the outer-wall.

The hoods are simply pushed into the screwed frame and fixed with two small screws.

### Technical data

Material	aluminium
Dimensions	235 mm x 205 mm x 72 mm
Colours	White, similar to RAL 9016 Anthracite, similar to RAL 7016

### Note

Products and illustrations may vary slightly. Due to continuous product development and/or several suppliers e.g. for raw materials, colours, among other things, may vary slightly (not for visible parts) or be shown differently in brochures.



Outer hood white 1/HWE



Outer hood anthracite 1/HAZ



e<sup>2</sup> and Ne<sup>Xt</sup> two-way outer screen  
1/HWE-2 or 1/HAZ-2