

**AIR & WATER TIGHT BUTYL
TAPE**

Internal & External use



Technical data

Properties	Performance	Standard
Carrier	Modified butyl	
Release film	Silicone coated pe	
Temperature range	-40°C to 90°C	-40°F to 194°F
UV tested	6 month	
Storage	Cool and dry	
Colour	Grey	
Application temperature	-10°C / 14°F	
Sd value	100	EN ISO 125752
Vapour Permeance	0.04 US Perm	ASTM E96
Resistance to water penetration	W1	EN 13859
Air tightness testing	$a_n < 0.1$	EN 1026

Application areas

Partel BUTAFLEX is used to create permanent air and water tight seals at penetrations of any size and can also be used for joining various materials. BUTAFLEX can be used internally or externally because of its unique properties.

Adheres to all Partel interior and exterior membranes, concrete, plaster, wood, steel, other vapour control layers including PE, PA, PP and aluminium, wood base panels OSB, MDF, plywood.

Application process

Ensure surface is clear from dust, grease, and loose material. The substrate must to be dry and free from frost. Prime surface with Partel ACRAPRIME and allow sufficient time for primer to dry depending on conditions. This will eliminate dust particles and result with a better bond.

Cut the required length for connection, peel the release liner from tape and with sufficient downward pressure press tape onto substrate, use Partel HELPING HAND to apply pressure evenly.

Advantages

Adhesion to all Partel interior and exterior membranes, concrete, plaster, wood, steel, other vapour control layers including PE, PA, PP and aluminium, wood base panels OSB, MDF, plywood.

A smoother physical substrate will result in optimum adhesion between tape and surface.

- Elastic—can be moulded to surfaces
- Excellent ageing resistance
- Water repelling carrier
- Split release backing for ease of installation
- Adheres to timber, masonry, concrete, PVC, metal, Partel membranes
- Design life = lifetime
- Lowest VOC rating in hazardous substance test

General information

Connection joints should be free from tensile strain. Acrylic base adhesive tapes are pressure activated, sufficient pressure is required to ensure a long lasting bond. A smoother physical substrate will result in optimum adhesion between tape and surface. It is the responsibility of the applicator to check the substrate for suitability, adhesion tests are recommended in non standard situations.

Ordering information

Name	Dimension	Dimension	Units / box
EXOSEAL 200	50mm x 5m	2" x 16-5"	20

"The information provided is based on current knowledge and experience. This data sheet may become invalid and we reserve the right to make changes to designs and processes as we continually improve quality. Processing instructions including full system component details should be adhered to.

Visit partel.com for the most up to date information"



WWW.PARTEL.IE
SALES@PARTEL.IE
TEL: 0818 33 33 55



WWW.PARTEL.CO.UK
SALES@PARTEL.CO.UK
TEL: 02037 401918



WWW.PARTEL.COM
SALES@PARTEL.COM
TEL: 888 487 1012