

## NAIL SEALING TAPE

seals between battens and Exoperm exterior membranes. Prevents water ingress during construction and afterwards.



### Technical data

Properties	Performance	
Carrier	Special PE foam	
Adhesive	Acrylic water resistant	
Temperature range	-40°C to 80°C	-40°F to 176°F
UV tested	6 months	
Storage	Cool and dry	
Colour	Black	
Application temperature	-10° C / 14° F	

### Application areas

Partel NAILSeal is used to create permanent watertight seal between EXOPERM membranes and battens.

### Application process

Ensure surface is clear from dust, grease, and loose material. The substrate must to be dry and free from frost.

Cut the required length for connection, peel the release liner from tape and with sufficient downward pressure press tape onto substrate to activate acrylic adhesive, use Partel HELPING HAND to apply pressure evenly. Apply the battens afterwards.

## Advantages

A smoother physical substrate will result in optimum adhesion between tape and surface

- High Performance tape
- Prevents damage to ExoPerm from screw or nail holes
- Optimum level of Acrylic adhesive with excellent ageing resistance
- Water repelling carrier—does not absorb water
- Adheres to timber, masonry, concrete, PVC, metal, Partel membranes
- Design life = lifetime
- Lowest VOC rating in hazardous substance test

## General information

Connections joints should be free from tensile strain. Acrylic base adhesive tapes are pressure activated, sufficient pressure is required to ensure a long lasting bond. A smoother physical substrate will result in optimum adhesion between tape and surface. It is the responsibility of the applicator to check the substrate for suitability, adhesion tests are recommended in non standard situations.

## Ordering information

Name	Dimension	Dimension	Units / box
CONEXO 60	66mm x 20m	2-1/2" x 65'-5/8	8

*"The information provided is based on current knowledge and experience. This data sheet may become invalid and we reserve the right to make changes to designs and processes as we continually improve quality. Processing instructions including full system component details should be adhered to. Visit [partel.com](http://partel.com) for the most up to date information"*